

STANDARD CABLE CLAMPS



Light-weight, open-rear design

SHELL SIZE	STRAIGHT CLAMP		90°		CABLE ENTRY	
	LOW-COST	SELF-LOCKING	LOW-COST	SELF-LOCKING	MAX.	MIN.
8	M85049/52-1-8*	M85049/52S8*	M85049/51-1-8*	M85049/51S8*	.204 (5.18)	.125 (3.18)
10S, 10SL	M85049/52-1-10*	M85049/52S10*	M85049/51-1-10*	M85049/51S10*	.286 (7.26)	.187 (4.75)
12, 12S	M85049/52-1-12*	M85049/52S12*	M85049/51-1-12*	M85049/51S12*	.416 (10.57)	.291 (7.39)
14, 14S	M85049/52-1-14*	M85049/52S14*	M85049/51-1-14*	M85049/51S14*	.476 (12.09)	.351 (8.92)
16, 16S	M85049/52-1-16*	M85049/52S16*	M85049/51-1-16*	M85049/51S16*	.626 (15.88)	.501 (12.72)
18	M85049/52-1-18*	M85049/52S18*	M85049/51-1-18*	M85049/51S18*	.706 (17.93)	.518 (13.16)
20	M85049/52-1-20*	M85049/52S20*	M85049/51-1-20*	M85049/51S20*	.831 (21.11)	.581 (14.76)
22	M85049/52-1-22*	M85049/52S22*	M85049/51-1-22*	M85049/51S22*	.956 (24.28)	.644 (16.36)
24	M85049/52-1-24*	M85049/52S24*	M85049/51-1-24*	M85049/51S24*	1.081 (27.46)	.706 (17.93)
28	M85049/52-1-28*	M85049/52S28*	M85049/51-1-28*	M85049/51S28*	1.187 (30.15)	.750 (19.05)
32	M85049/52-1-32*	M85049/52S32*	M85049/51-1-32*	M85049/51S32*	1.250 (31.75)	.875 (22.23)
36	M85049/52-1-36*	M85049/52S36*	M85049/51-1-36*	M85049/51S36*	1.375 (34.93)	.938 (23.83)
40	M85049/52-1-40*	M85049/52S40*	M85049/51-1-40*	M85049/51S40*	1.500 (38.10)	.938 (23.83)

\* Select plating code to match connector plating.

N = Electroless Nickel-Plated Aluminum Alloy

W = Olive Drab Chromate over Cadmium over Electroless Nickel-Plated Aluminum Alloy

S = Stainless Steel

	DESCRIPTION	PART NUMBER PREFIX	STRAIGHT	90°	45°
	Heat Shrink Boot Adapter → See pages 491-492	M85049/60	X		
	Environmental	M85049/7			X
		M85049/9		X	
		M85049/11	X		
	EMI/RFI Non-Environmental	M85049/23			X
		M85049/24		X	
		M85049/25	X		
	EMI/RFI Environmental	M85049/6			X
		M85049/8		X	
		M85049/10	X		
	EMI/RFI Crimp Ring	M85049/26	X		
	EMI/RFI Banding	M85049/82	X		
		M85049/83			X
		M85049/84		X	
	Cable Tie	M85049/55		X	
		M85049/53	X		
		M85049/54			
	Wire Seal	M85049/31	X		
	Compression Nuts "E"				

**Note:** If military standard versions won't fit your applications, please contact us with your requirements.

All dimensions in inches (millimeters in parenthesis)